

NOIDA METRO RAIL CORPORATION

Tender No: Open E- Tender No. NMRC/Telecom/2024/334 “Replacement of Existing Passenger Information Display System at Aqua Line of NMRC with Integrated PIDS Software and Hardware System

CORRIGENDUM No 1

<u>S. No</u>	<u>Page No</u>	<u>Clause No</u>	<u>Existing Clause</u>	<u>Modified Clause to the bid document</u>																														
				2 Passenger Display System per station i.e. total of 21 (stations) x 2 = 42 PIDS system at concourse level at 21 stations are already available and needs to be integrated with proposed PIDS solutions. Specifications of existing concourse PIDS are as below:																														
1	19/10	2.3.8 Annexure-A	2 Passenger Display System per station i.e. total of 21 (stations) x 2 = 42 PIDS system at concourse level at 21 station.	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">Type</th> <th style="width: 50%;">Specification</th> </tr> </thead> <tbody> <tr> <td>Application</td> <td>Indoor</td> </tr> <tr> <td>Active Display Size</td> <td>43" (Single sided)</td> </tr> <tr> <td>Backlight</td> <td>Direct backlight for LED</td> </tr> <tr> <td>Resolution</td> <td>1920(RGB) x1080 (FHD)</td> </tr> <tr> <td>Brightness</td> <td>700 cd/m²</td> </tr> <tr> <td>Contrast Ratio</td> <td>3000 : 1</td> </tr> <tr> <td>Response Time</td> <td>8 ms</td> </tr> <tr> <td>Viewing Angle</td> <td>Horizontal 178° and vertical 178°</td> </tr> <tr> <td>Colors</td> <td>16.7M(8-bit)</td> </tr> <tr> <td>Display Area</td> <td>941.2*529.4mm</td> </tr> <tr> <td>Audio Capability</td> <td>I/O input output, 2* Built-in speakers</td> </tr> <tr> <td>Intelligent Temperature Control System</td> <td>Intelligent temperature control function, auto-adjusting forced air cooling control system according to the internal temperature</td> </tr> <tr> <td>Timing On-off</td> <td>Free set Multi-period time</td> </tr> <tr> <td>Abnormal Voltage Protection</td> <td>Provide detection for internal voltage. It'll self-flooding for protection once it deviates from the standard value range</td> </tr> </tbody> </table>	Type	Specification	Application	Indoor	Active Display Size	43" (Single sided)	Backlight	Direct backlight for LED	Resolution	1920(RGB) x1080 (FHD)	Brightness	700 cd/m ²	Contrast Ratio	3000 : 1	Response Time	8 ms	Viewing Angle	Horizontal 178° and vertical 178°	Colors	16.7M(8-bit)	Display Area	941.2*529.4mm	Audio Capability	I/O input output, 2* Built-in speakers	Intelligent Temperature Control System	Intelligent temperature control function, auto-adjusting forced air cooling control system according to the internal temperature	Timing On-off	Free set Multi-period time	Abnormal Voltage Protection	Provide detection for internal voltage. It'll self-flooding for protection once it deviates from the standard value range
Type	Specification																																	
Application	Indoor																																	
Active Display Size	43" (Single sided)																																	
Backlight	Direct backlight for LED																																	
Resolution	1920(RGB) x1080 (FHD)																																	
Brightness	700 cd/m ²																																	
Contrast Ratio	3000 : 1																																	
Response Time	8 ms																																	
Viewing Angle	Horizontal 178° and vertical 178°																																	
Colors	16.7M(8-bit)																																	
Display Area	941.2*529.4mm																																	
Audio Capability	I/O input output, 2* Built-in speakers																																	
Intelligent Temperature Control System	Intelligent temperature control function, auto-adjusting forced air cooling control system according to the internal temperature																																	
Timing On-off	Free set Multi-period time																																	
Abnormal Voltage Protection	Provide detection for internal voltage. It'll self-flooding for protection once it deviates from the standard value range																																	

				<table border="1"> <tr> <td>Intelligent Optical Sensor</td> <td>With automatic function of light sensing. Self-regulation of screen brightness according to the light intensity of environment.</td> </tr> <tr> <td>Outdoor Grade</td> <td>IP54(waterproof & dustproof in high level),sunlight readable , no blacking</td> </tr> <tr> <td>Power Input</td> <td>AC 208V-240V</td> </tr> <tr> <td>Power Consumption</td> <td>300W</td> </tr> <tr> <td>Working Temperature</td> <td>20- 55°C</td> </tr> <tr> <td>Working Humidity</td> <td>5%~95% Non-condensing</td> </tr> <tr> <td>Storage Temperature</td> <td>20 to 60°C</td> </tr> <tr> <td>Dimension(WxDxH)</td> <td>1090(W)x803(H)x220(D)mm</td> </tr> <tr> <td>Weight</td> <td>85 Kg Approximate</td> </tr> <tr> <td>Protected Glass</td> <td>6mmAR Laminated glass</td> </tr> <tr> <td>Housing</td> <td>1.2mm galvanized steel Support,</td> </tr> <tr> <td>Anti-corrosion Paint</td> <td>powder painting 50000hours</td> </tr> <tr> <td>MTBF</td> <td>20mins</td> </tr> <tr> <td>MTTR</td> <td>Support</td> </tr> <tr> <td>Light Sensor</td> <td>Support</td> </tr> <tr> <td>Temperature Control</td> <td>Support</td> </tr> <tr> <td>Timer</td> <td>Support</td> </tr> <tr> <td>CPU</td> <td>Intel 1.86GHz</td> </tr> <tr> <td>Memory</td> <td>4GB</td> </tr> <tr> <td>Hard Disk</td> <td>SSD, 120G</td> </tr> <tr> <td>Operating System</td> <td>Linux</td> </tr> <tr> <td>Ethernet</td> <td>RJ 45</td> </tr> <tr> <td>Video Interface</td> <td>VGA,HDMI</td> </tr> <tr> <td>I/O Interface</td> <td>COM contact pin *2</td> </tr> <tr> <td>Video Playback</td> <td>Support MPEG-2/4、 H.264、 AVCHD</td> </tr> <tr> <td>Audio Playback</td> <td>Support WAV\MP3 file, Stereo playback</td> </tr> <tr> <td>Picture Playback</td> <td>Support BMP、 PNG、 GIF、 JPEG</td> </tr> <tr> <td>Language</td> <td>Hindi and English</td> </tr> </table>	Intelligent Optical Sensor	With automatic function of light sensing. Self-regulation of screen brightness according to the light intensity of environment.	Outdoor Grade	IP54(waterproof & dustproof in high level),sunlight readable , no blacking	Power Input	AC 208V-240V	Power Consumption	300W	Working Temperature	20- 55°C	Working Humidity	5%~95% Non-condensing	Storage Temperature	20 to 60°C	Dimension(WxDxH)	1090(W)x803(H)x220(D)mm	Weight	85 Kg Approximate	Protected Glass	6mmAR Laminated glass	Housing	1.2mm galvanized steel Support,	Anti-corrosion Paint	powder painting 50000hours	MTBF	20mins	MTTR	Support	Light Sensor	Support	Temperature Control	Support	Timer	Support	CPU	Intel 1.86GHz	Memory	4GB	Hard Disk	SSD, 120G	Operating System	Linux	Ethernet	RJ 45	Video Interface	VGA,HDMI	I/O Interface	COM contact pin *2	Video Playback	Support MPEG-2/4、 H.264、 AVCHD	Audio Playback	Support WAV\MP3 file, Stereo playback	Picture Playback	Support BMP、 PNG、 GIF、 JPEG	Language	Hindi and English
Intelligent Optical Sensor	With automatic function of light sensing. Self-regulation of screen brightness according to the light intensity of environment.																																																											
Outdoor Grade	IP54(waterproof & dustproof in high level),sunlight readable , no blacking																																																											
Power Input	AC 208V-240V																																																											
Power Consumption	300W																																																											
Working Temperature	20- 55°C																																																											
Working Humidity	5%~95% Non-condensing																																																											
Storage Temperature	20 to 60°C																																																											
Dimension(WxDxH)	1090(W)x803(H)x220(D)mm																																																											
Weight	85 Kg Approximate																																																											
Protected Glass	6mmAR Laminated glass																																																											
Housing	1.2mm galvanized steel Support,																																																											
Anti-corrosion Paint	powder painting 50000hours																																																											
MTBF	20mins																																																											
MTTR	Support																																																											
Light Sensor	Support																																																											
Temperature Control	Support																																																											
Timer	Support																																																											
CPU	Intel 1.86GHz																																																											
Memory	4GB																																																											
Hard Disk	SSD, 120G																																																											
Operating System	Linux																																																											
Ethernet	RJ 45																																																											
Video Interface	VGA,HDMI																																																											
I/O Interface	COM contact pin *2																																																											
Video Playback	Support MPEG-2/4、 H.264、 AVCHD																																																											
Audio Playback	Support WAV\MP3 file, Stereo playback																																																											
Picture Playback	Support BMP、 PNG、 GIF、 JPEG																																																											
Language	Hindi and English																																																											
<u>2</u>	<u>31 & 32</u>	<u>2.12.4.2 (j) & (s)</u>	<p>Operating Temperature (Ambient) : up to 70 C</p> <p>Storage: 1 TB SSD or better</p>	<p>Operating Temperature (Ambient) : up to 60 C</p> <p>Storage: 256 GB or better</p>																																																								

3	14 & 15	2.4.2.24 Annexure C : Schedule of Requirement (Tentative) Supply of server, Work station and media converter	1. Server for the OCC and BCC	<p>1. Server for the OCC and BCC with following specifications</p> <table border="1"> <thead> <tr> <th>S/N</th> <th>Description</th> <th>Specification</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Server Model and Make</td> <td>HPE/DELL</td> </tr> <tr> <td>2</td> <td>Processor</td> <td>Intel (R) Xeon (R) silver 4208 CPU @ 2.10 GHZ</td> </tr> <tr> <td>3</td> <td>Memory</td> <td>32 GB DDR5 or better</td> </tr> <tr> <td>4</td> <td>Storage</td> <td>1 TB (if zone level recording) RAID1 2 TB (if circuit level recording) RAID1</td> </tr> <tr> <td>5</td> <td>Optical Drive</td> <td>DVD-RW Optical Drive</td> </tr> <tr> <td>6</td> <td>OS</td> <td>Windows Server 2019 or Linux based</td> </tr> </tbody> </table>	S/N	Description	Specification	1	Server Model and Make	HPE/DELL	2	Processor	Intel (R) Xeon (R) silver 4208 CPU @ 2.10 GHZ	3	Memory	32 GB DDR5 or better	4	Storage	1 TB (if zone level recording) RAID1 2 TB (if circuit level recording) RAID1	5	Optical Drive	DVD-RW Optical Drive	6	OS	Windows Server 2019 or Linux based
			S/N	Description	Specification																				
			1	Server Model and Make	HPE/DELL																				
2	Processor	Intel (R) Xeon (R) silver 4208 CPU @ 2.10 GHZ																							
3	Memory	32 GB DDR5 or better																							
4	Storage	1 TB (if zone level recording) RAID1 2 TB (if circuit level recording) RAID1																							
5	Optical Drive	DVD-RW Optical Drive																							
6	OS	Windows Server 2019 or Linux based																							
2. Work Station for OCC and BCC	<p>2. Work Station for OCC and BCC with following specifications</p> <table border="1"> <thead> <tr> <th>S/N</th> <th>Description</th> <th>Specification</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Workstation Model and Make</td> <td>HPE/DELL</td> </tr> <tr> <td>2</td> <td>Processor</td> <td>13th Gen Intel® Core™ i7-13700, 16 cores</td> </tr> <tr> <td>3</td> <td>Memory</td> <td>16 GB DDR5 or better</td> </tr> <tr> <td>4</td> <td>Storage</td> <td>500 GB , 7200RPM, SATA, HDD, RAID1</td> </tr> <tr> <td>5</td> <td>OS</td> <td>Windows 10 or Windows 11</td> </tr> </tbody> </table>	S/N	Description	Specification	1	Workstation Model and Make	HPE/DELL	2	Processor	13th Gen Intel® Core™ i7-13700, 16 cores	3	Memory	16 GB DDR5 or better	4	Storage	500 GB , 7200RPM, SATA, HDD, RAID1	5	OS	Windows 10 or Windows 11						
S/N	Description	Specification																							
1	Workstation Model and Make	HPE/DELL																							
2	Processor	13th Gen Intel® Core™ i7-13700, 16 cores																							
3	Memory	16 GB DDR5 or better																							
4	Storage	500 GB , 7200RPM, SATA, HDD, RAID1																							
5	OS	Windows 10 or Windows 11																							
3 Station Server in TER	<p>3 Station Server in TER</p> <table border="1"> <thead> <tr> <th>S/N</th> <th>Description</th> <th>Specification</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Workstation Model and Make</td> <td>HPE/DELL</td> </tr> <tr> <td>2</td> <td>Processor</td> <td>13th Gen Intel® Core™ i7-13700, 16 cores</td> </tr> <tr> <td>3</td> <td>Memory</td> <td>16 GB DDR5 or better</td> </tr> <tr> <td>4</td> <td>Storage</td> <td>1 TB , 7200RPM, SATA, HDD, RAID1</td> </tr> <tr> <td>5</td> <td>OS</td> <td>Windows 10 or Windows 11 Windows Server 2019 or Linux based</td> </tr> </tbody> </table>	S/N	Description	Specification	1	Workstation Model and Make	HPE/DELL	2	Processor	13th Gen Intel® Core™ i7-13700, 16 cores	3	Memory	16 GB DDR5 or better	4	Storage	1 TB , 7200RPM, SATA, HDD, RAID1	5	OS	Windows 10 or Windows 11 Windows Server 2019 or Linux based						
S/N	Description	Specification																							
1	Workstation Model and Make	HPE/DELL																							
2	Processor	13th Gen Intel® Core™ i7-13700, 16 cores																							
3	Memory	16 GB DDR5 or better																							
4	Storage	1 TB , 7200RPM, SATA, HDD, RAID1																							
5	OS	Windows 10 or Windows 11 Windows Server 2019 or Linux based																							

			4. Station MMI IN SCR	<p>4. Station MMI IN SCR with following specifications</p> <table border="1"> <thead> <tr> <th colspan="3">Recommended PIDS MMI Hardware Spec</th> </tr> <tr> <th>S/N</th> <th>Description</th> <th>Specification</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Workstation Model and Make</td> <td>HPE/DELL</td> </tr> <tr> <td>2</td> <td>Processor</td> <td>13th Gen Intel® Core™ i7-13700, 16 cores</td> </tr> <tr> <td>3</td> <td>Memory</td> <td>8 GB DDR5 or better</td> </tr> <tr> <td>4</td> <td>Storage</td> <td>500GB , 7200 RPM, SATA, HDD</td> </tr> <tr> <td>5</td> <td>OS</td> <td>Windows 10 or Windows 11</td> </tr> </tbody> </table>	Recommended PIDS MMI Hardware Spec			S/N	Description	Specification	1	Workstation Model and Make	HPE/DELL	2	Processor	13th Gen Intel® Core™ i7-13700, 16 cores	3	Memory	8 GB DDR5 or better	4	Storage	500GB , 7200 RPM, SATA, HDD	5	OS	Windows 10 or Windows 11
Recommended PIDS MMI Hardware Spec																									
S/N	Description	Specification																							
1	Workstation Model and Make	HPE/DELL																							
2	Processor	13th Gen Intel® Core™ i7-13700, 16 cores																							
3	Memory	8 GB DDR5 or better																							
4	Storage	500GB , 7200 RPM, SATA, HDD																							
5	OS	Windows 10 or Windows 11																							
			5. NMS Server Work Station at OCC and BCC /CSS	<p>5. NMS Server Work Station at OCC and BCC /CSS</p> <table border="1"> <thead> <tr> <th colspan="3">Recommended PIDS MMI Hardware Spec</th> </tr> <tr> <th>S/N</th> <th>Description</th> <th>Specification</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Workstation Model and Make</td> <td>HPE/DELL</td> </tr> <tr> <td>2</td> <td>Processor</td> <td>13th Gen Intel® Core™ i7-13700, 16 cores</td> </tr> <tr> <td>3</td> <td>Memory</td> <td>8 GB DDR5 or better</td> </tr> <tr> <td>4</td> <td>Storage</td> <td>500GB , 7200 RPM, SATA, HDD</td> </tr> <tr> <td>5</td> <td>OS</td> <td>Windows 10 or Windows 11</td> </tr> </tbody> </table>	Recommended PIDS MMI Hardware Spec			S/N	Description	Specification	1	Workstation Model and Make	HPE/DELL	2	Processor	13th Gen Intel® Core™ i7-13700, 16 cores	3	Memory	8 GB DDR5 or better	4	Storage	500GB , 7200 RPM, SATA, HDD	5	OS	Windows 10 or Windows 11
Recommended PIDS MMI Hardware Spec																									
S/N	Description	Specification																							
1	Workstation Model and Make	HPE/DELL																							
2	Processor	13th Gen Intel® Core™ i7-13700, 16 cores																							
3	Memory	8 GB DDR5 or better																							
4	Storage	500GB , 7200 RPM, SATA, HDD																							
5	OS	Windows 10 or Windows 11																							

4. The KEY DATES LINKED TO PAYMENT MILESTONE as per RFP clause No.2.4.2.23 (Annexure- B) stands modified as given below:

Key Dates	Time to achieve in months from date of acceptance of Notice of Award	Description	Remarks
KD-1	2	Successful Demonstration of PIDS System at One station of NMRC	Payment i.e.15% of cost of Supply, Installation, Testing and Commissioning of PIDS System will be released to the satisfaction of NMRC
	2 to 3	FAT/FAI	

KD-2	4 to 6	Supply of Double Face ,2 Line PIDS panel for platforms	<p>Payment i.e. 30 % of cost of Supply, Installation, Testing and Commissioning of PIDS System will be released to the satisfaction of NMRC</p> <p>Cluster 1 : (7 Stations) – 10%</p> <p>Cluster 2 : (7 Stations) – 10%</p> <p>Cluster 3 : (7 Stations) – 10%</p>
KD-3	7 to 8	<p>Dismantling of Existing platforms PIDS panel and accessories and shifting to Telecom stores at NMRC Depot Greater Noida</p> <p>Installation of Double Face,2 Line PIDS Panel at Platforms of each station for all 21 stations of NMRC and Software Integration of existing Concourse PIDS and PAS.</p>	<p>Payment i.e. 30 % of cost of Supply, Installation, Testing and Commissioning of PIDS System will be released to the satisfaction of NMRC</p> <p>Cluster 1 : (7 Stations) – 10%</p> <p>Cluster 2 : (7 Stations) – 10%</p> <p>Cluster 3 : (7 Stations) – 10%</p>
KD-4	9 to 10	Final Commissioning of PIDS system at all 21 Stations of NMRC	<p>Payment i.e. i.e. 15 % of cost of Supply, Installation, Testing and Commissioning of PIDS System will be released with entire satisfaction of NMRC</p>

KD-5	22 (1 st Yr DLP) & 34 (2 nd Yr DLP) respectively	Defect Liability Period (DLP) support for 2 years	Balance payment i.e. 10% of cost of Supply, Installation, Testing and Commissioning of PIDS System will be released with entire satisfaction of NMRC in following manner: a. 5% : At the end of 1st Year DLP b. 5% : At the End of 2 nd Year DLP
------	---	---	--

This Corrigendum forms the part of the tender document (Technical Bid) and is required to be submitted duly signed and stamped by the bidders while submitting the bid to NMRC.

Date: 16.08.2024

Noida Metro Rail Corporation Ltd

Place: Noida